

Shrinkwrap

Packaging Systems

LAUNDRY L SEALER

Shrinkwrap LL70 & LL70SA



*Shrinkwrap LL70
Manual L Sealer*

Laundry L Sealer Features;

- Manual or semi automatic/air assisted operation options
- Impulse heated sealing wire to achieve optimum cutting and sealing performance
- Occupying minimal workspace, requiring only one operator
- Mounted on wheels for ease of movement
- Adjustable film rack to accommodate varying film widths
- Sealing table moves back, forth, up & down to facilitate random pack sizes
- For use with Polythene film
- One year warranty on non consumable parts
- British designed and built
- CE Marked

Unit 4, 145 Sterte Road, Poole, Dorset, UK, BH15 2AF
t: + 44 (0) 1202 674944 f: + 44 (0) 1202 671891
e: sales@shrinkwrap.co.uk
w: www.shrinkwrap.co.uk

Laundry L Sealer

The laundry L sealer is available in two variants: a manual version which will process laundry packs at up to 180 packs per hour, dependant on the operator and size of pack and the semi automatic/air assisted version which will speed up the process to approximately 300 packs per hour. An optional outfeed conveyor can be added.

Machine operation	Centre folded polythene is loaded onto a mandrel mounted on the right side of the machine. Film is fed through rollers and split over and under the product loading table. Product is loaded into the envelope of film and moved over to the sealing area by the operator. The sealing head is then pulled down and held down by the operator and the cut and seal takes place. On the semi auto/air assisted version the sealing head is held down by a pneumatic cylinder allowing the operator to prepare the next pack for wrapping.
Sealing system	Impulse heated L shape cutting and sealing wire mounted on a sealing head.
Pack adjustment	The machine sealing area is adjustable to cope with a range of pack sizes and depths. The sealing head moves back and forth and the height of the sprung loaded sealing table can be moved up and down with a simple lever.
Construction	Designed and built in the UK specifically to cope with the demanding environment of a commercial laundry.
Options:	Mounted on feet Outfeed conveyor

<i>Laundry L Sealer</i>	<i>Shrinkwrap LL70 Manual Operation</i>	<i>Shrinkwrap LL70SA Semi Automatic/Air Assisted</i>
Machine Dimension mm	L1860 x W1100 x H1130	L1860 x W1100 x H1130
Maximum Sealing Dimension mm	L700 x W750	L700 x W750
Maximum Pack Height mm	300	300
Maximum Film Width mm	900	900
Weight	195 kg	185 kg
Voltage/Air	220 V, 50/60Hz 13 amp single phase supply	220 V, 50/60Hz. 13 amp single phase supply 65psi (4.5bar)



Unit 4, 145 Sterte Road, Poole, Dorset, UK, BH15 2AF
 t: + 44 (0) 1202 674944
 f: + 44 (0) 1202 671891
 e: sales@shrinkwrap.co.uk
 w: www.shrinkwrap.co.uk



Distributed By;